



Itron Intelis wireless M-Bus

The Core of our Water Management Platform

Intelis combines last end ultrasonic measurement technology with high performing radio frequency communication to help Water Utilities in revenue protection. With no moving parts, the Intelis allows for protection against unplanned maintenance costs and provides accurate measurement over the entire product life. Integrated AMR offers the benefits of taylored functionalities within a mobile and fixed collection system.

FEATURES AND BENEFITS

- » High metrology accuracy & repeatability
- » Low pressure drops
- » No metering of air
- » Insensitive to sand or other particles in water
- » IP68, replaceable battery
- » Battery life time up to 15 years
- » Water temperature measurement
- » Standard wireless M-Bus protocol

Technology

- » High end static technology for revenue protection
 - Highly accurate measurement of consumption, temperature, aids leak, air detection...
 - Long life to mitigate against unplanned maintenance costs
 - Resistant to network accidents
- » Monitoring intelligence
 - Water Management efficiency
 - Flow profile, backflow and tampering alarms, all programmable thresholds, abnormal consumptions...
- » Installations
 - Any position
 - IP 68 permanent immersion (acc. EN60529)
 - Direct sunlight exposure
 - Tamper resistant thanks to Integrated construction & insensitive to magnetic fields

Communication

- » Integrated radio technology for mobile or fixed network collection systems (AMR)
- » Inductive communication for metrology verification
- » Optical pulse output for automatic test bench verification

Approval and standards

- » MID, Directive 2014/32/UE
- » European Standard EN14154:2007
- » International Standard ISO 4064:2014
- » OIML R49 2005
- » Directive 2014/53/EU
- » ACS certification (compliance for potable drinking water)



ENVIRONNEMENTAL-ECO DESIGN


Itron has adopted an eco-design approach. Ecodesign consists of taking the environmental impact of a product into account, over the whole of its lifecycle and in relation to various environmental aspects, while maintaining its functionality.

The Intelis was designed to provide our customers with a more environmentally friendly product. A life cycle assessment study was carried out to meet this challenge.

The recycling process has been optimised by creating a product that is easy to dismantle into separate components (batteries, PCB, brass...).

MULTIFUNCTIONAL DISPLAY

- » Easy to read display
- » Visual alarms
- » Configurable display sequence





Intelis LCD display

Encryption

- 1 Main display 8/9 digits
 - Index
 - Flowrate
 - Date & Time indication
 - Alarm
 - ...

- 2 Air in pipe indicator
- 3 System or application Alarm indicator
- 4 Leakage indicator
- 5 Test mode indicator Recalibration indicator
- 6 Battery level indicator
- 7 Volume unit indicator (Blinking when flowrate detected)
- 8 Flowrate unit indicator

COMMUNICATION

Radio Side	
Protocol	Wireless M-Bus according to EN 13757-3 & EN 13757-4
Operation mode	T1/C1
Frequency band	Compliant with OMS Annex 0, PHY-A/PHY-B 434,75/868,95MHz
Duty cycle	1%
Chiprate	Typ. 100 kcps

AES 128, Mode 5

Intelis integrates Itron Radio Technology.

This opens up to a large range of advanced and reliable AMR systems:

- » Radio walk-by systems
- » Radio fixed data collection systems


Automatic radio meter reading increases the reading reliability and significantly enhances the data acquisition speed.

The radio reading also opens accessibility to all meters even if the customer is absent or in hard to read locations.


Technical Characteristics


Nominal Diameter DN		mm	1	5	2	0	2	5	32	40	50
		inches	1/2	2"	3/	4"	1	"	1"1/4	1"1/2	2"
Approved dynamic Ratio = Q_3 / Q_1			160 200 250	160 200 250 315 400	160 200 250 315 400	160 200 250 315 400 500 630	160 200 250 315 400	160 200 250 315 400	160 200 250 315 400	160 200 250 315 400	160 200 250 315 400
Permanent flow rate	Q_3	m³/h	1.6	2	.5	4	6.3	1	0	16	25
Starting flow		l/h		4	2			6		1	5
Minimum flow rate	Q_1	l/h		6	.4			12.5		4	-0
Overload flow rate	Q_4	m³/h	2	3.1	25	5	7.9	12	2.5	20	31
Nominal pressure	MAP	bar					16				
Permanent temperature	MAT	°C					+0.1 / +70				
Head Loss Class		bar	0,4	0,:	25	0,63	0.4	0.0	63	0.4	0.63

TYPICAL ACCURACY CURVE Q3=2,5 M3/H




HEAD LOSS





DIMENSIONS

Nominal Diameter	mm	15	20	25	32	40	50
Α	mm	110 - 165 - 170	130 - 190	260	260	300	300
G	inches	G ¾ B	G1B	G1 ¼ B	G1 ½ B	G2B	G2 ½ B
В	mm			93			
С	mm			93			
D	mm			46.5			
Е	mm	17		25	5.4	33	37.6
F	mm	96		98	3.6	10	6.5
Н	mm	113		12	24	139.5	144.1



ENHANCED FUNCTIONALITIES

24.198 ^{m³}	Index	Record total volume of water consumed
1.24 ^{R3/H}	Instantaneous flow rate	Measure current flow rate over the last minute
AIR	Air in pipe	Air is detected, meter stop counting
	Backflow	Total volume measured under back flow is recorded
	Broken pipe	Flow rate reaches abnormal flow rate for a minimum time
	Flow repartition	Real flow rate is recorded according to operational segments
₫!	Leakage	Flow rate never goes under a minimum value Number of days with leakage is stored
	Battery alarm	Product battery is ending, when 12 months are left
1	Peak flow	Record 5 highest flow rates
	Minimum flow	Record 5 lowest flow rates
	Peak temperature	Record 5 highest Water Temperature
	Alarm water temperature	Configuration low and High temperature alarms
	Time synchronization	Walk by / Drive by: Meter clock re-synch at every read Fixed network : daily automatic clock re-synchronization
	Volume below threshold	Total consumption below a low flow-rate threshold
	Volume above threshold	Total consumption above a high flow-rate threshold
40	Time of use	Registers consumption within a defined intervals of the year
	Logging intervals	Record consumption hour/day/week/month intervals 54, 108, 216 intervals configurable storage
	Reversed meter	Alarm if > 1000l in reverse flow have been recorded
	Meter stopped	Alarm if no consumption over a configurable period has been recorded
	Fraud	When someone tries to open the meter
112 112	Custom billing period	Store volume index at 4 preset dates
<u> </u>	Alarm reconfiguration	Store events of reconfiguration of a meter via radio Reconfiguration event is recorded.
Friday 31	Event log	Last critical alarms are recorded date stamped



Join us in creating a more **resourceful world**. To learn more visit **itron.com**

While Itron strives to make the content of its marketing materials as timely and accurate as possible, Itron makes no claims, promises, or guarantees about the accuracy, completeness, or adequacy of, and expressly disclaims liability for errors and omissions in, such materials. No warranty of any kind, implied, expressed, or statutory, including but not limited to the warranties of non-infringement of third party rights, title, merchantability, and fitness for a particular purpose, is given with respect to the content of these marketing materials. © Copyright 2017 Itron. All rights reserved. WA-0102.5-EN-06.17

ITRON WATER METERING

9, rue Ampère 71031 Mâcon cedex France

Phone: +33 3 85 29 39 00 **Fax:** +33 3 85 29 38 58